

ENTIRE SPECTRUM OF TOOLS FOR SOIL TILLAGE

Indestructible tillage machines

www.rolmako.com


This presentation is to make it easier for our dealers and farmers to choose the right agricultural machinery starting with recognizing the right working tools, appropriate chisels, plough share and discs for the specific crop and the effect that the user needs to obtain.

In this publication, each working element of a tillage cultivator, stubble cultivator, disc harrow, or subsoiler has been accompanied by a description of its cultivation function, soil on which it should operate as well as its maximum working depth.











CHAPTER ISeedbed cultivators
Tillage cultivators

CHAPTER IIDisc harrows

CHAPTER III
Subsoilers
Looseners



Seedbed cultivators Tillage cultivators

Machines whose primary working elements are tines for pre-sowing and stubble cultivation, mixing of natural fertilisers, no-till work, and other agrotechnical operations.

The purpose of the cultivator depends on the type of the working tines used. Tillage machines with versatile applications are equipped with a plough beam compatible with various working attachments adapted to different field operations.
























The choice of an agricultural cultivator is dictated by the field conditions, in which it is to work and the cultivation effect that we want to achieve. The most important component of the machine determining the final result of work are the working elements and overload protection.


TINES

At Rolmako, when designing new devices, we pay much attention to the selection of working elements in terms of the economy and quality of cultivation.



As complete as possible range of soil tillage cultivators on the market

The choice of an agricultural cultivator is dictated by the field conditions, in which it is to work and the cultivation effect that we want to achieve. The most important component of the machine determining the final result of work are the working elements and overload protection.



Working elements should be operated as shallow as possible so as to achieve the intended cultivation effect

Seedhed cultivators Tillage cultivators





















Not recommended for the given may not be satisfactory

Depending on the compactness, soil is divided into:

compact soils – clays and loams

 slightly-compacted soils – slightly loamy sands medium-compacted soils - clay sands and dust in loose soils - loose sand and gravel



Single springs made of a rod with a diameter 7 or 8 mm



ActiVAgro weeder

Maximum depth: 3 cm

Power demand:



Purpose, cultivation effect:

Mechanical removal of weeds that along with the roots are pulled to the surface of the soil

Cultivation functions:

- Ultra-shallow tillage
- Aeration and broking of soil crust
- Grassland tillage (raking turf and destroying molehills)
- Mixing of mineral fertilisers with soil

Intended use of the working element due to the compactness of the s										
	loose	soils	slightly-com	pacted soils	medium-compacted soil		compacted soil			
	1 2			3 4		6	7	8		





SU 32x12 mm tine with reinforcement*

- Coulter 35x200x5 mm
- Wide coulter 100 mm**
- *) the reinforcement for U 659 cultivator is an option, for other machines it is standard.
- **) available for the U 382 machine

Application in machines:

- Machines mounted on the tractor's front three-point linkage
- Tillage cultivator U 382
- Seedbed cultivator U 659
- Compact seedbed cultivator U 684
- BigField system carrier

Maximum depth: 12 cm

Power demand:



Purpose, cultivation effect:

• Levelling and rolling of the soil

- Pre-sowing cultivation, weed infestation regulation
- Mixing of mineral fertilisers with soil
- Mixing of liquid organic fertilisers with soil

Intende	ed use of t	he workir	ng elemer	nt due to t	he compa	ctness of	the soil
loose	soils	slightly-compacted soils		medium-compacted soil		compacted soil	
loose soils		3 4		5	6	7	8

Seedbed cultivators Tillage cultivators























may not be satisfactory

Depending on the compactness, soil is divided into:

compact soils – clays and loams

 slightly-compacted soils – slightly loamy sands medium-compacted soils - clay sands and dust in loose soils - loose sand and gravel





SN 45x10 mm deflected tine

- Coulter 35x210x6 mm
- Wide coulter 120 mm

Application in machines:

■ Pre-sowing cultivator U 445 VibroSTAR



Maximum depth: 12 cm

***** Power demand:

Purpose, cultivation effect:

• Levelling and rolling of the soil

Cultivation functions:

- Pre-sowing cultivation, weed infestation regulation
- Mixing of mineral fertilisers with soil
- Mixing of liquid organic fertilisers with soil

Intend	ed use of	the worki	ng elemei	nt due to t	he compa	ictness of	the soil
loose	e soils	slightly-compacted soils		medium-coi	mpacted soil	compacted soil	
1	2	3	4	5	6	7	8





SA 45x12mm straight tine, coulter 40x215x6mm (reinforcement optional)



Application in machines:

- Compact seedbed cultivator U 684
- BigField system carrier

Maximum depth: 12 cm

**** Power demand:

Purpose, cultivation effect:

Levelling and rolling of the soil

- Pre-sowing cultivation, weed infestation regulation
- Mixing of mineral fertilisers with soil
- Mixing of liquid organic fertilisers with soil

Intende	d use of t	he workin	ig elemen	t due to tl	ne compa	ctness of	the soil
loose	soils	slightly-compacted soils		medium-corr	pacted soil	compacted soil	
1 2		3	4	5	6	7	8

Seedhed cultivators Tillage cultivators















It can operate on this soil, the effect of the work should for a given type of soil

Not recommended for the given may not be satisfactory

Depending on the compactness, soil is divided into:

compact soils - clays and loams medium-compacted soils - clay sands and dust in loose soils - loose sand and gravel

slightly-compacted soils – slightly loamy sands





SG tine with spring plough beam 25x25mm, coulter with a width of 260mm



Maximum depth: 12 cm

Application in machines:

BigField system carrier

Power demand:



Purpose, cultivation effect:

- Levelling and rolling of the soil
- Good mixing and cutting of weeds over the entire surface, also in case of shallow cultivation

Cultivation functions:

- Pre-sowing cultivation, weed infestation regulation
- Mixing of mineral fertilisers
- Mixing of liquid organic fertilisers with soil
- The tine is also recommended for the cultivation of vegetables and sugar beets

Intended use of the working element due to the compactness of the soil slightly-compacted soils | medium-compacted soil compacted soil





SX tine with reinforced double spring 50x10mm, coulter with a width of 260mm



Application in machines:

- Compact seedbed cultivator U 684
- BigField system carrier

Maximum depth: 12 cm

Power demand:



Purpose, cultivation effect:

- Levelling and rolling of the soil
- Good mixing and cutting of weeds over the entire surface, also in case of shallow cultivation

- Pre-sowing cultivation, weed infestation regulation
- Mixing of mineral fertilisers
- Mixing of liquid organic fertilisers with soil
- The tine is also recommended for the cultivation of vegetables and sugar beets

Intende	Intended use of the working element due to the compactness of the soil								
loose	soils	slightly-compacted soils		medium-com	pacted soil	compacted soil			
1 2		3	4	5	6	7	8		

Seedbed cultivators Tillage cultivators





Legend



















Depending on the compactness, soil is divided into:

compact soils – clays and loams medium-compacted soils - clay sands and dust in loose soils - loose sand and gravel

slightly-compacted soils – slightly loamy sands





SS 45x12 mm tine, 255x50x6 mm



Maximum depth: 15 cm

**** Power demand:

Purpose, cultivation effect:

• Tillage and mixing at medium depth

Cultivation functions:

- Pre-sowing cultivation, weed infestation regulation
- Mixing of mineral fertilisers with soil
- Mixing of liquid organic fertilisers with soil

Intended use of the working element due to the compactness of the soil											
loos	e soils	slightly-compacted soils		medium-cor	npacted soil	compa	ted soil				
1	2					7	8				





SW 70x12 mm tine with reinforcement*

■ Coulter 300 x 52 x 7 mm or goosefoot with a width of 180 mm *) the reinforcement is optional



Application in machines:

- Tillage cultivator mounted on the front three-point linkage
- Universal cultivator U 497
- BigField system carrier



Maximum depth: 15 cm

Power demand:



Purpose, cultivation effect:

- Tillage and intensive mixing at medium depth
- The effect of a wide cutting for the variant with goosefeet

- Mixing of solid organic fertilisers with soil, e.g. manure
- Stubble tillage

Intende	d use of t	he workin	ne working element due to the compactness of the soil					
loose	soils	slightly-compacted soils		medium-corr	pacted soil	compacted soil		
1 2		3	4 5 6 7		7	8		

Seedhed cultivators Tillage cultivators




















Not recommended for the given may not be satisfactory

Depending on the compactness, soil is divided into:

compact soils - clays and loams

 slightly-compacted soils – slightly loamy sands medium-compacted soils - clay sands and dust in loose soils - loose sand and gravel





Tine ST 90x13 mm with reinforcement*

■ Coulter 300 x 60 x 10mm or goosefoot with a width of 280 mm *) the reinforcement is optional

Application in machines:

- Universal cultivator U 497
- BigField system carrier

Maximum depth: 15 cm

**** Power demand:

Purpose, cultivation effect:

- Tillage and intensive mixing at medium depth
- The effect of a wide cutting for the variant with goosefeet

Cultivation functions:

- Pre-sowing cultivation, weed infestation regulation
- Mixing of mineral fertilisers with soil and liquid organic fertilizers, e.g. liquid manure
- Mixing of solid organic fertilisers with soil, e.g. manure
- Stubble tillage





Double springs made of a rod with a diameter of 16 mm, length of the harrow finger 750 mm

Rolmako EasyFix system (MADE IN GERMANY) fast and economically justified regeneration of working elements (multiple regeneration)



Application in machines:

SpringExpert mulch harrow

Maximum depth: 4 cm

***** Power demand:

Purpose, cultivation effect:

- Mechanical removal of weeds that along with the roots are pulled to the surface of the soil
- Stopping evaporation
- It allows more water to be retained in the soil

- Ultra shallow stubble tillage
- Grassland tillage (raking of turf and destruction of molehills)
- Stimulating the germination of self-seeding cereals and rapeseed

Intended use of the working element due to the compactness of the soil										
loos	e soils	slightly-compacted soils		medium-co	mpacted soil	compacted soil				
1 2		3	4	5	6	7	8			

Seedhed cultivators Tillage cultivators















Legend







Depending on the compactness, soil is divided into:

compact soils - clays and loams medium-compacted soils - clay sands and dust in loose soils - loose sand and gravel

slightly-compacted soils – slightly loamy sands





ProCut knife roller

Application in machines:

- ProCut knife roller mounted on the front three-point linkage
- U 693 compact disc harrow
- U 652 disc harrow
- U 436 multifunctional tillage cultivator
- SpringExpert mulch harrow

Maximum depth: 3 cm

**** Power demand:

Purpose, cultivation effect:

 Intensive shredding of crop residues and aftercrop plants

Cultivation functions:

- Cutting aftercrops and crop residues that will comprise the mulch cover. Chopped straw and leaves are easier to be covered and mixed in subsequent stubble operations
- Destruction of maize borer larvae in maize stubble







Vogel & Noot tine with double-sided heart-shaped coulter, spring plough beam 35x35 mm or Non-Stop protection

Application in machines:

U 453 stubble cultivator









Power demand:



Purpose, cultivation effect:

• Tillage and intensive mixing at medium depth

- Mixing of mineral fertilisers with soil
- Mixing of liquid organic fertilisers with soil
- Mixing of solid organic fertilisers with soil
- Stubble tillage

Intende	ed use of	the workii	ng elemer	nt due to t	he compa	ictness of	the soil
loose	soils	slightly-compacted soils		medium-compacted soil		compacted soil	
1 2		3	4	5	6	7	8

Seedhed cultivators Tillage cultivators
















for a given type of soil



Not recommended for the given may not be satisfactory

Depending on the compactness, soil is divided into:

compact soils - clays and loams

 slightly-compacted soils – slightly loamy sands medium-compacted soils - clay sands and dust in loose soils - loose sand and gravel





Lemken tine with a divided coulter, spring plough beam with Non-stop protection*

*) solution also available with Vogel&Noot system



Application in machines: U 453 stubble cultivator

Maximum depth: 15 cm

Power demand:

Purpose, cultivation effect:

 Intensive shredding of crop residues and aftercrop plants

Cultivation functions:

- Mixing of mineral fertilisers with soil
- Mixing of liquid organic fertilisers with soil
- Mixing of solid organic fertilisers with soil
- Stubble tillage







Tine for ploughless tillage with spring plough beam 35x35 mm



Application in machines:

U 436 multifunctional tillage cultivator

Maximum depth: 15 cm

**** Power demand:

Purpose, cultivation effect:

• Tillage and intensive mixing at medium depth

- Mixing of mineral fertilisers with soil
- Mixing of liquid organic fertilisers with soil
- Mixing of solid organic fertilisers with soil
- Stubble tillage

Intende	Intended use of the working element due to the compactness of the soil									
loose	soils	slightly-com	pacted soils	medium-cor	npacted soil	compacted soil				
1	2	3	4	5	6	7	8			



Delta tine with Non-stop protection (straight mouldboard)

Standard equipment:

Side wing stubble shares intended for operation at a depth of up to 15 cm

Application in machines:

U 436 multifunctional tillage cultivator

Maximum depth: 35 cm

Power demand: ★★★★★☆☆☆

Purpose, cultivation effect:


- Cultivation and intensive mixing
- Stubble cultivation and deep ploughless tillage

Cultivation functions:

- Mixing of mineral fertilisers with soil
- Mixing of liquid organic fertilisers with soil
- Mixing of solid organic fertilisers with soil
- Stubble tillage
- Deep ploughless tillage



Intended use of the working element due to the compactness of the										
loos	e soils	slightly-compacted soils		medium-compacted soil		compac	compacted soil			
1										



AgriFlex with Non-stop protection (twisted mouldboard)

Standard equipment:

Side wing stubble shares intended for operation at a depth of up to 15 cm

Application in machines:

U 436 multifunctional tillage cultivator

Maximum depth: 35 cm

Power demand:

Purpose, cultivation effect:


- Cultivation and intensive mixing
- Stubble cultivation and deep ploughless tillage

Cultivation functions:

- Mixing of mineral fertilisers with soil
- Mixing of liquid organic fertilisers with soil
- Mixing of solid organic fertilisers with soil
- Stubble tillage
- Deep ploughless tillage



Intend	led use of	the work	ing eleme	nt due to	the comp	actness o	f the soil	
loos	e soils	slightly-co	mpacted soils	medium-co	mpacted soi	compacted soil		
1	2	3	4	5	6	7	8	



AgriFlex tine with Non-stop protection with a narrow 40 mm coulter*

*) standard AgriFlex tine is equipped with 80 mm chisel

The chisel after the extension can work together with a seeder to create a combination of cultivation and fertilisation

Application in machines:


U 436 multifunctional tillage cultivator

Maximum depth: 35 cm

Purpose, cultivation effect:

- Cultivation and intensive mixing
- Stubble cultivation and deep ploughless tillage

- Mixing of mineral fertilisers with soil
- Mixing of liquid organic fertilisers with soil
- Mixing of solid organic fertilisers with soil
- Stubble tillage
- Deep ploughless tillage
- Tillage with simultaneous sowing of fertiliser



Seedbed cultivators
Tillage cultivators



AVAILABILITY TABLE



www.rolmako.com



Item	Machine	Tines / coulters available
1.	Tillage cultivator mounted on the front three-point linkage	SW
2.	Tillage cultivator U 382	straight SU / deflected SU
3.	Seedbed cultivator U 659	straight SU / deflected SU
4.	Pre-sowing cultivator U 445 VibroSTAR	deflected SN
<u>5.</u>	Compact seedbed cultivator U 684	SU / SA / SG / SX
6.	Compact seedbed cultivator U 684 PRO	SU / SA / SG / SX
7.	Universal cultivator for pre-sowing and stubble	SS / SW / ST
	cultivation U 497	
8.	BigField system carrier	SU / SA / SG / SX
		SS / SW / ST
9.	Stubble cultivator U 453	Vogel & Noot type tine / Lemken type tine
10	AA 025 - 12 - 120 - 02 - 120 - 120 -	
10.	Multifunctional tillage cultivator U 436	tine for ploughless tillage with spring
		plough beam 35x35 mm
		Delta tine for ploughless tillage
		AgriFlex tine for ploughless tillage
11.	SpringExpert mulch harrow	double spring fingers with a thickness of 16 mm and length of 750 mm
12.	ActivAgro weeder	single spring fingers with a thickness of 7 mm

Disc Harrows

All machines with working elements in the form of cultivation discs, comprise a group of machines that are characterized by low power demand and relatively low wear of working elements in relation to the cultivation performed.

The individual disc harrows differ from each other with the distance between each disc sections, attacking angle of working elements and type of the shock absorption system applied.




Working elements in the form of rotating discs have many advantages, which translate into numerous benefits for the user of the device.

The most important thing is the low resistance coefficient, which has a positive effect on the power demand and wear and tear of components.

DISC EQUIPMENT

Machines equipped with cultivation discs can perform many tasks on the farm; from pre-sowing to post-harvest soil cultivation. Disc harrows are useful when mixing organic and mineral fertilisers with soil. They are also applied for ploughless tillage. It is a multi-task machine used for many purposes on every farm.



As complete as possible range of disc harrows on the market

Disc harrows















Depending on the compactness, soil is divided into:

compact soils - clays and loams

 slightly-compacted soils – slightly loamy sands medium-compacted soils - clay sands and dust in loose soils - loose sand and gravel







Application in machines:

U 622 light disc harrow

Maximum depth: 15 cm

Power demand:



Purpose, cultivation effect:

- A universal solution that is a compromise between pre-sowing and stubble cultivation
- Optimal use of the machine on the farm

Cultivation functions:

- Mixing of mineral fertilisers with soil
- Mixing of liquid organic fertilisers with soil
- Mixing of solid organic fertilisers with soil
- Pre-sowing cultivation
- Stubble tillage

Intended use of the working element due to the compactness of the soil							
loose	e soils	slightly-con	npacted soils	medium-cor	npacted soil	compa	cted soil
1				5	6		8

*) purpose, cultivation effect, and functions are described for the standard disc with an aggressive tine.





Disc 510 mm / 560 mm rubber shock absorber 40x180 mm

Application in machines:

- Disc harrow on the front three-point linkage
- U 693 compact disc harrow
- U 645 harrow for vineyards and orchards
- U 652 disc harrow (560 mm)

Maximum depth: 15 cm



Power demand:

Purpose, cultivation effect:

- A universal solution that is a compromise between pre-sowing and stubble cultivation
- Optimal use of the machine on the farm

- Mixing of mineral fertilisers with soil
- Mixing of liquid organic fertilisers with soil
- Mixing of solid organic fertilisers with soil
- Pre-sowing cultivation
- Stubble tillage

Intended use of the working element due to the compactness of the soil							
loose	soils	slightly-com	oacted soils	medium-compacted soil		compacted soil	
1	2	3	4	5	6	7	8

Disc harrows
















Recommended for a given type of soil





Depending on the compactness, soil is divided into:

compact soils – clays and loams
 slightly-compacted soils – slightly loamy sands
 medium-compacted soils – clay sands and dust
 loose soils – loose sand and gravel

......







Application in machines:

U 652 disc harrow

Maximum depth: 15 cm

Power demand:

Purpose, cultivation effect:

 Best cutting and mixing effect. Recommended for all post-harvest cultivation, especially after maize harvested for grain

Cultivation functions:

- Mixing of mineral fertilisers with soil
- Mixing of liquid organic fertilisers with soil
- Mixing of solid organic fertilisers with soil
- Pre-sowing cultivation
- Stubble tillage

Intended use of the working element due to the compactness of the soil							
loose	soils	slightly-com	pacted soils	medium-compacted soil		compacted soil	
1							

*) purpose, cultivation effect, and functions are described for the standard disc with an aggressive tine.

**) optional, LongLife rubber shock absorber 40x180mm used as a standard version.





Disc 620 mm PRO+ plough beam LongLife rubber shock absorbers 50x210 mm

Application in machines:

Heavy stubble harrow U 671


Maximum depth: 15 cm

Purpose, cultivation effect:

- Recommended for all stubble cultivation, especially after maize harvested for grain
- At 7 cm working depth, the disc provides full-surface cutting of the stubble

- Mixing of mineral fertilisers with soil
- Mixing of liquid organic fertilisers with soil
- Mixing of solid organic fertilisers with soil
- Pre-sowing cultivation
- Stubble tillage
- Cultivation of fallow land

Intended use of the working element due to the compactness of the soil							
loose	soils	slightly-comp	pacted soils	medium-compacted soil		compacted soil	
1	2	3	4	5	6	7	8



Disc Twin Disc

purpose: cultivation after ploughing, rolling of soil after the main working elements of the tillage machine diameter: 470 mm
Hub: 30x30 mm axle with maintenance-requiring bearings thickness: 4 mm
Note: the corrugated discs are used in machines mounted on the tractor's front three-point linkage and in subsoilers as a tillage rear roller.



ALFA disc

purpose: stubble cultivation diameter: 560 mm hub: maintenance-free thickness: 5 mm Note: recommended for post-harvest cultivation after harvesting maize for grain, provides a better cutting result.



Smooth disc

purpose: pre-sowing cultivation diameter: 510 or 560 mm hub: requiring maintenance or maintenance-free thickness: 4 mm Note: on request.



Working disc with a large attacking angle

purpose: stubble cultivation and cultivation of fallow land diameter: 620 mm hub: maintenance-free thickness: 6 mm Note: best cutting effect and mixing is already available at 7 cm working depth.



Disc with fine toothed

purpose: pre-sowing cultivation and stubble cultivation diameter: 510 or 560 mm hub: requiring maintenance or maintenance-free thickness: 4 mm Note: on request.



Toothed disc standard (universal)

purpose: pre-sowing cultivation and stubble cultivation diameter: 510 or 560 mm hub: requiring maintenance or maintenance-free thickness: 4 mm Notes: the most universal use, standard disc for Rolmako harrows.



UltraCutter disc

Purpose: stubble cultivation hub: maintenance-free Note: shallow tillage 2-3 cm at high working speed 20 km/h.



Matrix Star

Purpose: cultivation between the rows (interrow cultivation), elimination of weeds, reduction of evaporation by tearing apart the topsoil hub: maintenance-free Remarks: The working element is especially recommended for soil crust areas.











Item	Machine	Available discs
1.	Disc harrow on the front three-point linkage	toothed 510 / 560 mm
2.	U 622 light disc harrow	toothed 510 / 560 mm with fine toothing 510 / 560 mm
3.	Compact disc harrow U 693	smooth 510 / 560 mm ALFA 560 mm
4.	U 693 SMART disc harrow	toothed 510 / 560 mm with fine toothing 510 / 560 mm smooth 510 / 560 mm
5.	Disc harrow for vineyards and orchards U 645	toothed 510 / 560 mm with fine toothing 510 / 560 mm smooth 510 / 560 mm
6.	U 652 disc harrow	toothed 560 / 610 mm with fine toothing 560 mm smooth 560 mm Alfa 560 mm
7.	Heavy stubble harrow U 671	
8.	Heavy stubble harrow U 671 PRO	toothed 620 mm



Rolmako Rolmako

www.rolmako.com

Subsoilers Looseners

Machines intended for loosening the soil in order to improve its physical and biological properties. Subsoilers loosen the soil layer untouched by ploughing, allowing better water soaking in it, mixing of fertilisers into deeper layers and their aeration, which promotes root development of plants. The working depth depends on the model of the machine in the range from 35 cm to 60 cm.























Classic, specialized subsoilers and versatile multi-purpose tillage machines


LOOSENING

Tines for important operations that improve water management and promote better soil aeration.

The use of the Rolmako subsoilers improves the soil structure, thanks to which the farmer achieves higher was a subsoilers improves the soil structure.

The use of the Rolmako subsoilers improves the soil structure, thanks to which the farmer achieves higher yield of agricultural crops. All water is absorbed into the soil, fertilisers penetrate the lower layers, positively influencing the development of plant roots.





The most complete offer of deep loosening machines on the market

Subsoilers Looseners


















It can operate on this soil, the effect of the work should

......



Depending on the compactness, soil is divided into:

compact soils - clays and loams

 slightly-compacted soils – slightly loamy sands medium-compacted soils - clay sands and dust in loose soils - loose sand and gravel



Straight tine with a chisel: 100 mm HARDOX

Application in machines:

U 602 universal subsoiler

Maximum depth: 60 cm

***** Power demand:

Purpose, cultivation effect:

- Deep loosening of the soil without turning it over
- Subsoilers equipped with a straight tine are designed to improve water regime in the soil and break the plough pan
- The loosening function is performed to a lesser extent

Cultivation functions:

- Breaking of the plough pan
- Improvement of water regimes in the soil (meliorative function – possibility of installing drainage balls)







Straight tine with a chisel 300 mm

Application in machines:

U 602 universal subsoiler

Maximum depth: 60 cm

**** Power demand:

Purpose, cultivation effect:

- Deep loosening of the soil without turning it over
- Subsoilers equipped with a straight tine are designed to improve water regime in the soil and break the plough pan
- The loosening function is performed to a lesser extent

- Breaking of the plough pan
- Improvement of water regimes in the soil (meliorative function – possibility of installing drainage balls)

Intended use of the working element due to the compactness of the soil							
loose	soils	slightly-com	pacted soils	medium-co	mpacted soil	compac	ted soil
1	2	3	4	5	6	7	8

Subsoilers Looseners











......











Depending on the compactness, soil is divided into:

compact soils - clays and loams

 slightly-compacted soils – slightly loamy sands medium-compacted soils - clay sands and dust in loose soils - loose sand and gravel



Subsoiler with a deflected Michel type tine, "small" version

Application in machines:

 Subsoiler with the coupler U 608 (coupler for rotary harrow or other accompanying machine)

Maximum depth: 35 cm

**** Power demand:

Purpose, cultivation effect:

- Deep cutting and loosening of the soil without turning it over
- Michel tines have a better loosening effect of soil compared to straight tines
- The meliorative function is performed to a lesser extent

Cultivation functions:

- Breaking of the plough pan
- Improvement of water regimes in the soil





Subsoiler with a deflected Michel type tine, "long" version

Application in machines:

- Subsoiler with the frame U 614
- Subsoiler with two rows of tines U 619

Maximum depth: 45 cm

**** Power demand:

Purpose, cultivation effect:

- Deep cutting and loosening of the soil without turning it over
- Michel tines have a better loosening effect of soil compared to straight tines
- The meliorative function is performed to a lesser extent

- Breaking of the plough pan
- Deep loosening of the soil without turning it over
- Improvement of water regimes in the soil

Intended use of the working element due to the compactness of the soil							
loose	soils	soils slightly-compacted soils medium-compacted soil		compacted soil			
1	2	3	4	5	6	7	8

Subsoilers Looseners
























Not recommended for the given type of soil, cultivation effect may not be satisfactory

Depending on the compactness, soil is divided into:

compact soils - clays and loams

 slightly-compacted soils – slightly loamy sands medium-compacted soils - clay sands and dust in loose soils - loose sand and gravel





Ripper tine

Standard equipment:

Side wing shares

Application in machines:

Chisel plough U 624

Power demand:

Maximum depth: 45 cm

Purpose, cultivation effect:

• Deep and intensive loosening and mixing of the soil

Cultivation functions:

- Mixing of mineral fertilisers with soil
- Mixing of liquid organic fertilisers with soil
- Mixing of solid organic fertilisers with soil
- Breaking of the plough pan
- Improvement of water regimes in the soil
- Deep ploughless tillage







Atlas tine, working elements with built-in cemented carbide

Standard equipment:

• Working elements welded with built-in cemented carbide as standard. Stubble share 300 mm as an option

Application in machines:

- Multi-purpose subsoiler U 638
- Subsoiler with the coupler U 632

Maximum depth: 35 cm

Power demand:

Purpose, cultivation effect:


- Deep soil loosening, with an optional
- Stubble share stubble cultivation with intensive mixing

- Mixing of mineral fertilisers with soil
- Mixing of liquid organic fertilisers with soil
- Stubble tillage
- Breaking of the plough pan Improvement of water regimes in the soil

Intended use of the working element due to the compactness of the soil							
loose	soils	slightly-com	pacted soils	medium-co	mpacted soil	compac	ted soil
1	2	3	4	5	6	7	8

CHAPTER III Subsoilers







www.rolmako.com














Item	Machine	Available tines		
1.	U 602 universal subsoiler	straight with a chisel 100 mm		
		straight with a chisel 300 mm		
2.	Subsoiler with the coupler U 608			
3.	Subsoiler with "V" frame: U 614	deflected Michel type		
4.	Subsoiler with two rows of tines U 619			
5.	U 624 chisel plough	Ripper		
6.	Multi-purpose subsoiler U 638	ALI		
7.	Subsoiler with the coupler U 632	Atlas		



Impact resistant boron steel

The basic standard of spare parts is the best price-quality ratio and high reliability. Working elements intended for average requirements as part of work on an individual farm.



Parts reinforced with abrasion resistant welds

Wear-resistant, high-quality, efficient and reliable.
Suitable for difficult operating conditions when
the machine is exposed to heavy loads. Deposition
welding applied on working elements is recommended
when working on soils that require above-average
wear and at heavy loads of working tools during service
work or in case of shared use of the equipment on severa
farms.



Working elements armed with cemented carbide

Extreme working conditions and heavy loading of the machine sound like a daily struggle for you? The plough parts with built-in cemented carbide are just for you. Working elements armed with cemented carbide are recommended for the highest loads on large-scale farms or in case of cultivation services on soils that are free of stones. Cemented carbide blades allow to increase the service life of the working elements of a cultivator, or other machines used in soil cultivation, even up to 7 times.







Even the best-quality plough parts of the cultivator or the harrow discs will turn out to be faulty and ineffective without a properly selected shock absorber to protect the working components and the supporting frame against excessive load.

The choice of the shock absorber for the soil tillage implementations determines the success of the entire project.

The complete range of cultivation equipment has been achieved thanks to the introduction of many types

of the shock absorption by working elements that are designed to operate with various impact loads.



Division of tillage machines by the absorber



The shock absorber is the most important component of the entire plough system of the machine

Variants of shock absorbers protecting the working elements against excessive load



Auger

plough

beam

Rubber

shock

absorber

Pressure

springs

Hydraulic

shock

absorber

Torsion

springs

Vibrating

working

lements

Torsion springs Auger plough beam ActivAgro Compact seedbed Weeder cultivator U 684 SpringExpert Compact seedbed mulch harrow cultivator U 684 PRO Disc harrow U 652 BigField system carrier U 453 stubble cultivator U 436 multifunctional tillage cultivator **Rolmako** www.rolmako.com

Vibrating working elements

Tillage cultivator mounted on the front three-point linkage

U 382 tillage cultivator

U 659 seedbed cultivator

Pre-sowing cultivator
U 445 VibroSTAR

Compact seedbed cultivator U 684

Compact seedbed cultivator U 684 PRO

U 497 universal cultivator for pre-sowing and stubble tillage

BigField system carrier

U 622 light disc harrow

Rubber shock absorber

Disc harrow mounted on the front three-point linkage

U 693 disc harrow

ProCut knife roller

U 645 disc harrow for vineyards and orchards

> U 652 disc harrow

U 671 heavy stubble harrow

U 671 PRO heavy stubble harrow

> BigField system carrier

Pressure springs

U 453 stubble cultivator

U 436 multifunctional tillage cultivator

U 638 multi-purpose subsoiler

U 632 multi-purpose subsoiler

Hydraulic shock absorber

U 602 universal subsoiler

U 608 subsoiler with the coupler U 608

U 614 subsoiler with the "V" frame

U 624 chisel plough with Ripper tine

SHOCK ABSORBERS

Working tools that complement cultivation-







Looseners operating before the basic working elements of the machine







Crossboard drags in different variants







Spring combs















Rear rollers supporting the operation of cultivation tools

Pressing, compacting the soil, crushing clods and levelling the field surface are intended to complete the cultivation following the operation of working tools of cultivation machines, this task is taken over by the rear roller. The selection of the right tillage roller has a great influence on the entire work process and the characteristics of the application of a cultivating machine, which is why Rolmako provides a range of over 30 different cultivating rollers differing in the shape and type of material used, outer diameter, weight, and most importantly, cultivation purposes. The choice of the rear roller depends on the soil that we have and the effect that we want to achieve. At Rolmako, we provide professional consulting services during the configuration of agricultural equipment aiming at the proper adaptation of the soil tillage implemention to the conditions in which it is to operate.



